



## A safe route outside.

The EscapeSet for a 2nd escape route  
from **Becker**.



**BECKER**  
Together it's easier.



## Feel safe in the event of an emergency

A second escape route is now a requirement in an increasing number of buildings and leaving the building through a window or patio door is an easy option. However, solutions that involve the use of electric drives need to be reliable – even in the event of a power cut.

The new EscapeSet from Becker allows users to easily comply with the requirement for an additional escape route. The blinds can be raised easily and quickly in any situation thanks to the crank installed inside the building. This ensures that you can always safely escape outside.

The drive automatically detects its end positions again after using the crank, without it having to be recalibrated. The crank is only used to turn the drive when operating it for the first time during installation. Afterwards, it is discretely and securely stored in a holder next to the window.



### Ready to use in the event of an emergency

Have all of the blinds been lowered and the route to the front door is blocked by fire? And have you also lost power to the drive? This is where the EscapeSet comes into play. The crank allows you to raise the blinds quickly and easily.

The EscapeSet ensures that the building is well-equipped to handle an emergency situation and gives its residents a feeling of security.



## Highlights of the EscapeSet

- Quick opening even in the event of a loss of power
- Optimal gear ratio between the crank and drive
- The crank only turns with the drive when operating it for the first time during installation
- Drive with sensitive obstacle and blockage detection
- The drive automatically detects its end positions, even after it has been operated with the crank
- Suitable for use with roller shutters installed in various different areas

## Contents of the EscapeSet

- Drive with electronic limit switch 12 Nm or 20 Nm, depending on the set
  - C-Plug (3 m)
  - Wall bearing with catch
  - Mini strip
  - Roller shutter escape drive adapter set (contains ring S60L, output shaft adapter, drive adapter S60)
  - Roller shutter escape hand crank set (contains bevel gearbox for size 60 octagonal shafts, pivoting bearing with square bar 45° SW6, jointed crank 1m, crank bar holder)
- ▶ A universal gear holder and a base plate (85 x 85 mm) can be ordered as optional accessories.



**BECKER**

Becker-Antriebe GmbH

Drives and control units for roller  
shutters, sun protection and  
extended applications

Friedrich-Ebert-Straße 2 – 4  
D-35764 Sinn

Tel.: 02772/507-0  
Fax: 02772/507-151

[info@becker-antriebe.com](mailto:info@becker-antriebe.com)  
[www.becker-antriebe.com](http://www.becker-antriebe.com)

