

YOUR TIME, YOUR SUN PROTECTION, YOUR COMFORT!

Timer and sun protection control TC72

QUALITY made in Germany



THE SMART TIMER AND SUN PROTECTION CONTROL.

With the smart timer and sun protection control TC72, roller shutter and sun protection systems can be configured according to personal needs. Thanks to its simple operation and easy configuration, the TC72 offers maximum comfort. The sensors ensure the necessary accuracy when measuring threshold values. Additionally, besides the window light sensor, external sensors such as sun and wind sensors can be optionally integrated, allowing the TC72 to operate even more precisely.

Your benefits

- Commissioning, configuration, and operation possible via device buttons and free app
- No loss of switching times and set values in case of a power failure
- Automatic summer/winter time adjustment
- Vacation mode can be activated
- Large, illuminated display
- Switch between manual and automatic mode directly on the control device
- Can be installed in any flush-mounted device box Ø 58 mm according to DIN EN 49073 / DIN EN 60670
- Can be integrated into switch programs of many manufacturers
- Connection option for external signal transmitters such as smoke detectors, push buttons, or thermostats enables meaningful integration with central control systems

Highlights of the Roller Shutter Application

- Two freely selectable intermediate positions can be programmed
- Dusk function
- Pre-set switching times
- Up to 10 switching times per day can be programmed
- Astro function in the morning and evening eliminates the need to readjust the switching time
- Optional connection of the SC33 window light sensor and external sensors



COMFORT, JUST A TOUCH AWAY.

Setting the timer and threshold values for privacy and sun protection systems is also no problem, as the new Becker tool makes it guick and effortless.

Download the Becker tool now with ease:







Highlights of the Sun Protection Application

- Two freely selectable intermediate positions, including tilt function, can be programmed
- Can be used for awnings, screens, roller blinds, and other privacy and sun protection applications
- Automatic shading time can be individually adjusted
- Pre-set threshold values
- Blind Mode: Two intermediate positions or one intermediate position with tilt function can be programmed
- Blind Mode: Precise adjustment of the slat angle possible
- Optional connection of the SC71 wind sensor or the SC81 sun and wind sensor







BECKER-Antriebe GmbH

Drives and control units for roller shutters, sun protection and Extended Applications

Friedrich-Ebert-Straße 2–4 D-35764 Sinn

Tel.: 02772/507-0 Fax: 02772/507-110

www.becker-antriebe.com info@becker-antriebe.com

